

STENTOFON 92012 Master Control Station

Features

- Compact 12 Button Master
- Crisp, Clear Voice Communication
- Rugged, all Metal Rack Mount Housing
- Call Annunciation by Flashing LED and Tone
- Programmable All Call
- Lamp Test and Line Fault Test
- Stand-alone or Multiple Master Use
- Parallel Master or Interface with P-9600



Functional Description

The #92012 is a high quality rack mount intercom master capable of handling calls from and direct-select access up to (12) substations. It is designed to operate either by itself, in parallel with other masters or as a distributed remote master in a P-9600 intercom system. The 92012 is ideal for door control communication in jails and prisons, and as a building submaster in campus and building security systems. The 92021 will operate with all standard 9600 substations, on either STENTOFON 9200 or 9600 intercom systems.

Technical Specifications

Housing:	1/8" Aluminum rackmount faceplate, finished in black epoxy
Size:	5 1/4" H x 19" W x 6" D
Buttons:	(12) electronic selector buttons, with red and green LED indicators. Faceplate includes (4) function buttons and up/down volume controls.
Amplifiers:	(1) 24 watt output to substations, (1) 12 watt output to master.
Speaker:	3" round, 63 ohm, 200-5000 Hz
Microphone:	Electret condenser, -65dB @ 1 Kz sensitivity
Remote Control:	Provision for optional remote control board
Handset:	Provision for optional (9249) handset kit
Wiring:	Requires #92583 (12) pair cable and connector
Power:	Requires #1117 24 V DC 1.2 A power supply