

## STENTOFON 81250 Emergency/Security Telephone

### Features

- Durable G-style handset w/ magnetic switchhook
- Armored Cord
- Piezo Ringer
- Brushed Stainless Steel Faceplate
- Fully Sealed Front Panel
- Hearing-aid compatible



### Functional Description

The 82150 is a highly vandal-resistant and rugged telephone ideal for communication applications in harsh environments. The telephone can be mounted on a STENTOFON backbox (part number #1041 - stainless steel or #1042 high visibility yellow).

### Technical Specifications

|                        |   |
|------------------------|---|
| Faceplate Dimensions:  | 11 3/4" H x 8 1/2" W x 2.45" D  |
| Connectors:            | (2) Auxiliary Outputs<br>(1) RJ-11<br>(1) Power Connector   |
| Weight:                | 6 lbs.  |
| Panel:                 | 12 GA., 304 Stainless Steel brushed finish with (6) .203" mounting holes  |
| Operating Temperature: | -20° C to +60° C (Heater available for extreme climate conditions)  |
| Max Loop Resistance:   | 1500 Ohms (loop start operation)  |
| Power:                 | 5.5 to 25 VDC or derived from 110 VAC (Power Transformer provided)  |
| REN:                   | 1.1   |
| Signaling:             | Tone or Pulse   |
| Frequency Response:    | 300Hz - 3kHz  |
| *Mounting:             | Custom back-box (optional) comes in stainless steel or high visibility yellow (shown above).<br>(Stainless Steel - part #1041; High Visibility Yellow - part #1042) |